

ASG 83



Technical drawing of the front view of the unit. Dimensions are indicated in millimeters (mm):



- Overall width: 76,5
- Distance from left edge to first vertical line: 53
- Distance between first and second vertical lines: 53
- Distance between second and third vertical lines: 53
- Overall height: 214,5 w
- Distance from top edge to first horizontal line: 183
- Distance from first horizontal line to second horizontal line: 141,5
- Distance from second horizontal line to third horizontal line: 76,5
- Distance from bottom edge to first horizontal line: 61

A warning symbol (a lightning bolt inside a triangle) is located on the left side of the unit. A crossed wrench and screwdriver icon is located above the unit. A large double-headed vertical arrow is located below the unit, indicating height adjustment. A small icon of a person is located at the bottom right of the unit.

Kg / 24h - Water			
	38°	58	32°
	32°	64	21°
	21°	73	15°
	10°	83	10°



Stainless steel AISI 304



Air



Water

ASG 83

Dati tecnici – Caractéristiques techniques – Technical specifications – Datos técnicos – Technische Daten

Prod.Kg/24h +10°C - Prod.Lb/24h +10°C		80-176
Prod.Kg/24h +10°C - Prod.Lb/24h +10°C		83-183
Contenitore/Bac/Bin/Depósito/Behälter	Kg/Lb	25-55
Larghezza/Largeur/Width/Anchura/Breite	mm	485
Profondità/Profondeur/Depth/Profundidad/Tiefe	mm	586
Altezza/Hauteur/Height/Altura/Höhe	mm	720
Peso netto/Poids net/Net weight/Peso neto/Nettogewicht	Kg	55
Peso lordo/Poids brut/Gross weight/Peso bruto/Bruttogewicht	Kg	59
Vol. imballo/Vol.embal/Vol.(packed)/Volumen con embalaje/Verpackungsvolumen	m ³	0,30
Alimentazione/Voltage/Voltaje/Anschlussspannung	V/Hz/ph	230/50/1
Compressore/Compresseur/Compressor/Compresor/Kompressor	HP	1/4
Compressore/Compresseur/Compressor/Compresor/Kompressor (T evap.= -10°C)	W	343
Watt - Totale/Total/Total/Total/Gesamt (T = +43°C)	W	400
Calorie/Calorie/Calorie/Caloria/Kalorie cond.	Kcal / h	630
Ampère - Totale/Total/Total/Total/Gesamt	A	3
Fusibile/Fusible/Recommanded fuse/Fusible/Netzsicherung	A	10
Refrigerante/Réfrigérant/Cooling gas/Refrigerante/Kühlmittel	R	290
Carica/Charge/Fill/Carga/Füllmenge	Kg	0,069
eq. CO ₂	Kg	0,207
GWP		3
Carica/Charge/Fill/Carga/Füllmenge	Kg	0,047
eq. CO ₂	Kg	0,141
GWP		3
Entrata acqua/Entrée eau/Water inlet/Entrada agua/Wasseranschluß	Ø	3/4"
Scarico acqua/Vidange eau/Water outlet/Desague/Wasserabfluß	Ø	3/4"
Acqua/Eau/Water/Agua/Wasser - lt / h 21°C 15°C		4-16
Pressione acqua/Pression eau/Water pressure/Presión agua/Wasserdruck - bar	min / max	1 - 6
Temp.ambiente/Temp.ambient/Ambient temp./Temp.ambiente/Ramtemperatur - °C	min / max	10 - 40
Temp. acqua/Temp. eau/Water temp./Temp. agua/Wassertemperatur - °C	min / max	5 - 35